



GMSI24S ACOUSTIC WARNING

indoor alarm

Power 24Vdc

Protection: **IP55**

Noise level: 95 dB(A)



GMSI24S-FM ACOUSTIC WARNING

indoor alarm

Power 24Vdc

Protection: **IP55**

Noise level: 95 dB(A)

FM APPROVED Certified



GMLP24 - OPTICAL WARNING

indoor alarm

Power 24Vdc

Protection: **IP55**

GMLP24-FM - OPTICAL WARNING

indoor alarm

Power 24Vdc

Protection: **IP55**

FM APPROVED Certified



GMSE24-54-3 - OPTICAL/ACOUSTIC AUTOSUPPLIED WARNING

outdoor alarm

Power 24Vdc

Protection: **IP34**

Noise level: 108 dB(A)

No backup battery 12 VDC - 2.1 Ah

Complies with standard EN 54-3



GMSL24 - OPTICAL/ACOUSTIC WARNING

stroboscopic flashing outdoor alarm

with weather protection cover

Power 24Vdc

Protection: **IP55**

Noise level: 100/112 dB(A)





GMBT21A - BACKUP BATTERY 12 VDC - 2.1Ah

Nominal voltage 12V - Weight 890 g
 Size mm (LxWxD) 178 x 60 x 34 - Projection Faston 5mm
 Max discharge current 12.0A
 Max load current 0.500A



GMBT72A - BACKUP BATTERY 12 VDC - 7.2Ah

Nominal voltage 12V - Weight 2650 g
 Size mm (LxWxD) 151 x 94 x 65 - Projection Faston 5mm
 Max discharge current 43.2A
 Max load current 1.800A



GMFROH2-4-BL - SHIELDED MULTI-WIRES CABLE

hank FROH2R - **4 wires**
 diameter Ø = 0,5mm length 100m
CEI 20-22
 Suitable for external uses



GMFROH2-6-BL - SHIELDED MULTI-WIRES CABLE

hank FROH2R - **6 wires**
 diameter Ø = 0,5mm length 100m
CEI 20-22
 Suitable for external uses

GMREL24 - RELÈ 2 switch 24Vdc with plinth
 complete with base

